

LESSO



EV Charger

Mobile charge at any time



LSACS-C-32/220-B01

Easy switching among multi-gear currents

The default current is 32A, if this current is insufficient for charging at this time, you can adjust the charging current.

Strong compatibility and suitability for various models

Suitable for most new energy vehicle models.

Protection grade: IP55

It has an IP55 waterproof and dust-proof function, and always ensures the charging safety of your car, even in severe outdoor environments.



LSACS-C-32/220-B02

Reservation charging and avoiding peak hours

To take advantage of the cheap price and save on power, you may schedule a charging session for 1~10 hours

8 Safety features

Protection against overheating, overcurrent, leakage, overvoltage, output exception, CP fault, communication fault, and relay fault.

Compressive, strong and durable

The mainbox is made of high-strength PC material with strong, compressive resistance.

Technical parameter

Types	LSACS-C-32/220-B01	LSACS-C-32/220-B02
Output Power	7kW	
Rated Output Voltage	Two-phase 220VAC	
Rated Output Current	32A	
Display Mode	LED light	Display
Use Method	Swipe card/Bluetooth/Free vend(Optional)	
Plug Type	Type 2	
Rated Output Frequency	60Hz	
Insulation Resistance	>10MΩ	
Operation Temperature	-20°C~+50°C	
Cable Length	5m (customizable)	
Dimension	Control mainbox: 342 (L) * 214(M) * 116mm (H)	
Flame Retardant Rating	UL94-V0	
Standard	IEC 62196-1:2022, IEC 61851-1:2017	